



YORPOWER

RATING	MODEL	ENGINE
350kVA Canopied Set	YXP350D6S	Perkins®

GENERAL	
OUTPUT RATINGS 60Hz,	
Prime	350kVA, 280kW
Standby	385kVA, 308kW
ENGINE	PERKINS 2206A-E13TAG2
ALTERNATOR	LEROY SOMER



TECHNICAL DATA			
Engine Model	2206A-E13TAG2	Engine Speed	1800RPM
Cylinders	6	Fuel Cons: 100% Load (l/hr)	81
Displacement	12.5 Litres	Fuel Cons: 75% Load (l/hr)	62
Coolant Capacity	51.4 Litres	Oil Capacity	40 Litres
Cooling	Water Cooled	DBA @ 7M	69.3
Fuel Tank Capacity	661	Intake System	Turbocharged

These ratings are suitable for Prime Continuous power output at varying load with no limitation on annual hours of operation.
The Generator will supply 10% overload for 1 in 12 hours.

GENERAL ARRANGEMENT	

DIMENSIONS AND WEIGHTS			
Length mm	Width mm	Height Mm	Weight Kg
4242	1400	2470	4375

We reserve the right to amend specifications without notice. All ratings are at standard ISO conditions
Alternators may vary subject to lead time and availability

Registered Office:
Yorpower Limited
Unit 2, Hurricane Close
Sherburn In Elmet
LS25 6PB
UNITED KINGDOM



T: +44 (0) 1977 688155
F: +44 (0) 1977 688158
E: sales@yorpower.com
W: www.yorpower.com

Yorpower Limited, Registered in England and Wales No. 7035780