





RATING	MODEL	ENGINE
2000kVA Open Set	YXP2000RS	Serkins

GENERAL

OUTPUT RATINGS

50Hz, 400/230VOLT, 3PHASE

YXP2000 Prime 2000kVA, 1600kW YXP2200 Standby 2200kVA, 1760kW

ENGINE MODEL PERKINS

ALTERNATOR LEROY SOMER



TECHNICAL DATA				
Engine Model	4016TAG2A	Engine Speed	1500RPM	
Cylinders	16	Fuel Cons: 100% Load I/hr	434	
Cubic Capacity	61.12	Fuel Cons: 75% Load	316	
Aspiration	Turbocharged, Aftercooled	Cooling Air Flow : L/min	112	
Cooling	Water Cooled	Exhaust Gas Flow : m³/min	411	
Fuel Tank Capacity	N/A	Exhaust Gas Temp : °C	480	

These ratings are suitable for Prime Continuous power output at varying load with no limitation on annual hours of operation.

The Generator will supply 10% overload for 1 in 12 hours. Option for Stamford alternator available.

GENERAL ARRANGEMENT DIMENSIONS AND WEIGHTS Length Width Height Weight inc Lube Oil & Coolant Kg

We reserve the right to amend specifications without notice. All ratings are at standard ISO conditions

3432

2060

Registered Office: Yorpower Limited Unit 2, Hurricane Close Sherburn In Elmet LS25 6PB UNITED KINGDOM

4850



T: +44 (0) 1977 688155 F: +44 (0) 1977 688158 E: sales@yorpower.com

10503

W: www.yorpower.com