

Genset
Model: **YXP137RSC**

Enclosed set



Open set



Frequency	Phases	Power factor	Prime output	Standby output
50Hz	3	0.8	137 kVA / 110 kW	151 kVA / 121 kW

Ratings

- Prime output: This rating is applicable for supplying continuous electrical power at variable load. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.
- Standby output: This rating is applicable for supplying electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings.
- Standard reference conditions: 25°C, 100m A.S.L., 30% relative humidity.

Design features

- High quality assembly, providing stiffness and low vibration.
- Powder coated steel. Corrosion and scratch resistant.
- Compact and long service life.
- Wiring and connectors with double protection.
- Protection guards in radiator and high voltage parts.
- Full 12 month YorPower Warranty.

Design standards

- CE marking.
- ISO8528-1995.
- GB/T2820-1997.
- ISO 9001:2008 Registered Company.

Configuration

- 4-Stroke water-cooled diesel engine.
- Industrial silencer.
- Coolant recovery tank.
- Single bearing, 4 pole brushless alternator.
- Anti vibration mountings.
- Integral fuel tank with fully bounded base protection.
- Fuel level sensor.
- Auto start control system with electronic digital control module DSE7420 as standard.
- Output circuit breaker.
- Emergency stop button.
- High engine temperature and low oil pressure shutdown system.
- 12V starter battery with leads and switch.

Acoustic canopy features

- Water and dust proof design.
- Door locks.
- High quality sound absorbing and fire retardant inner material.
- Lifting lugs.
- Forklift holes in base.

** The images above are for illustration purposes only.


Engine data

Engine brand	Perkins	Total coolant capacity	37.22 Litres
Engine model	1006TAG	Total lub oil capacity	19 Litres
Engine Speed	1500 RPM	Cooling air flow	154 m ³ /min
Number of cylinders	6	Exhaust gas flow	25.71 m ³ /min
Aspiration	Turbo & Aftercooled	Exhaust gas temperature	585 °C
Combustion system	Direct injection	Fuel cons. @ 100% Standby load	34.6 l/hr
Displacement	5.99 Litres	Fuel cons. @ 100% Prime load	31.5 l/hr
Governor type	Mechanical	Fuel cons. @ 75% Prime load	24.1 l/hr
Cooling system	Water cooled	Fuel cons. @ 50% Prime load	16.5 l/hr

Alternator data

Alternator brand	Leroy Somer	Number of wires	12 re-connectable
Alternator model	LSA44.2M95	AVR model	R 250
Excitation	Self excited	Voltage regulation	± 0.5%
Insulation class	H	Total Harmonic distortion	< 2%
Drip proof protection	IP23	Telephone interference	TIF < 50%, THF < 2%
Winding pitch	2/3 (wdg 6)	Flanges and shield	Cast iron


Enclosed set data



L x W x H (mm) Weight Fuel tank Noise@7m

3338 x 1255 x 1843 2354 kg 420 Litres 70 db

Open set data



L x W x H (mm) Weight Fuel tank Noise@7m

2627 x 1036 x 1492 1564 kg 380 Litres 115 db

** Due to constant innovation, design and specifications are subject to change without notice. All weights, dimensions and noise levels are subject to a 10% tolerance.

Distributor Address:

YORPOWER

Yorpower Ltd,
Electricity Building, Unit 2 Hurricane Close,
Sherburn in Elmet, Leeds LS25 6PB, UK
T : +44 (0)1977 688155
E: sales@yorpower.com
www.yorpower.com